

Product No.:	<b>iTM133</b>
Order Information	<b>iTM133-H 13.3inch/1000nits Brightness/PCAP/12V</b>
<b>Display Parameters</b>	
LCD Size	13.3" TFT (LED Backlight)
Resolution	1920*1080
Brightness	1000cd/m <sup>2</sup>
Aspect ratio	16:9
Life Time	50,000hrs
Contrast Ratio	(500:1)
Response Time	8ms
Viewing Angle	Whole View Angle 80/60(U/D), 80/80(L/R)
Color Resolution	16.7M
<b>Touch Screen Parameters</b>	
Touch Type	PCAP Touch
Surface Hardness	6H>
Resolution	4096*4096
Life Time	50,000hrs
Transparent Rate	>85%
UV protection	Yes
<b>Degree of protection</b>	
Front Panel IP65	Default
Whole IP65	Optional
<b>IO Interface</b>	
DC	DC 12V
USB	1x USB2.0 For Touch
VGA	1x

HD MI	1x
<b>Power Supply</b>	
Power Supply	12V DC Power Input
Power Consumption	<30W
Wide Voltage	Optional (DC 6~36V Wide Voltage, IPTS )
<b>Installation</b>	
VESA	100mm*100mm
Embedded	Cabinet Hole Size(Optional)
<b>Environments</b>	
Operating Temp	-10°C~50°C
Storage Temp	-30°C~70°C
Relative Humidity	5~95%@10°C (Non-condensing)
Vibration	5~500Hz, 1.5G, 0.15mm peak value
Shake	1.5 Grms, IEC 60068-2-64, 5 ~ 500 Hz, 1 hr/axis
Shock	10 Grems, IEC 60068-2-64, Half sine wave, for 11 ms
EMC	CE/FCC Class A
<b>Enclosure</b>	
Housing Material	Steel
Dimensions	329 mm (W) x 201mm (D) x 67 mm (H)
Net Weight	2KG